



E-10S 93Wh Li-ion V-Mount Battery

The E-10S provides 14.8V, 6.3Ah and 93Wh of Lithium Ion power with a V-Mount connection as standard. It features an integrated 3-step LED Power Indicator to display the battery capacity status. Innovative design, lightweight and compact, the E-10S combines the highest standards of quality, safety and reliability.

E-10S Product Features:

- **3 Power Indicator LEDs** are located on the side of the E-10S for a quick and easy check to see if the battery is empty, full or requires charging. This can be checked at any time.
- **Battery circuit protection** ensures the E-10S is fully protected against common causes of battery misuse, guarding against over charge, over discharge, over current and exposure to high temperatures.
- **The highest grade Lithium Ion cells** are used to ensure the E-10S is one of the most reliable batteries available.
- **Most environmentally friendly** and safest battery in its classification.
- **Weighing only 1.65 lbs.**, the E-10S is compact and durable, ideal for regular use and transportation to and from location.
- **Attaching E-10S batteries** to cameras without a standard V-Mount connection is possible through the use of P-V2 and P-VS2 adaptor plates, available separately from IDX.
- **The E-10S can be fully recharged** quickly and safely using a sequential or simultaneous ENDURA charger.

Endura
SYSTEM



Technical Specification

Battery Capacity:

14.8V, 6.3Ah, 93Wh

Max. Output Voltage:

16.8V DC

Nominal Voltage:

14.8V DC

Maximum Discharge Current:

6.3Ah (69W)

End Voltage

11V

Battery Protection:

Over charge (reset)
Over discharge (reset)
Over current (reset)
Temperature protection (non reset)

Ambient Temperature:

To charge:
32°F ~ 113°F (50°F ~ 86°F recommended)
To discharge:
-4°F ~ 122°F (50°F ~ 104°F recommended)
To store:
-4°F ~ 140°F (32°F ~ 68°F recommended)

Dimensions:

3.35(W) x 5.59(H) x 1.97(D) inches

Weight:

1.65 lbs. approx.

IDX System Technology, Inc.
19001 Harbortgate Way, Suite 105
Torrance, CA 90501
U.S. A.
Telephone: (310) 328-2850
Fax: (310) 328-8202



For further information email us: idx.usa@idx.tv or visit our website www.idxtek.com
IDX reserves the right to change the specifications contained herein without notice.